

Condor 2100x Product List

		Product Name			
		Condor 2101x (Rear PMC Video. VME Style Pin-Out. Air Cooled and Conduction Cooled)	Condor 2101xF (Front Video. Air Cooled)	Condor 2104x (Rear PMC Video. VME Style Pin-Out. Air Cooled and Conduction Cooled)	Condor 2106xF (Front Video. Air Cooled)
Output Type	VGA	2	1 (fo)	2	1 (fo)
	DVI / HDMI	2	2 (fo)	2	2 (fo)
	RS-343	2	2 (fo)	2 (fo) (nre)	2 (fo)
	RS-170 (3 wire)	2 (nre)	2 (fo) (nre)	2 (fo)	2 (fo) (nre)
	STANAG 3350 A/B/C	2 (nre)	2 (fo) (nre)	2 (fo)	2 (fo) (nre)
	TV / RS-170 (1 wire)	1 (fo)	1 (fo)	1 (fo)	1 (fo)
	DisplayPort	NA	2 (mini) (Can be converted to VGA or Single-Link DVI using an off the shelf adapter or EIZO's Adapt product line)	NA	2 (mini) (fo) (Can be converted to VGA or Single-Link DVI using an off the shelf adapter or EIZO's Adapt product line)
Input Type	VGA	2	1 or 2 (pseudo) (fo)	1	NA
	DVI / HDMI	NA	NA	1	2 (fo)
	RS-343	2 (fo)	2 (fo)	1 (fo) (nre)	NA
	RS-170 (3 wire)	2 (fo) (nre)	2 (fo) (nre)	1 (fo) (nre)	NA
	STANAG 3350 A/B/C	2 (fo) (nre)	2 (fo) (nre)	1 (fo) (nre)	NA
	TV / RS-170 (1 wire)	2	2	1	NA
	HD-SDI	NA	NA	NA	2 (fo)

(fo) = Factory option

(nre) = Non-recurring engineering fee may be required

(pseudo) = Shared DDC. Uses EIZO Rugged Solutions' cable

(mini) = Mini DisplayPort

NA = Not Available

Note: Maximum two video inputs and two video outputs at a time.